

403182300300

Miniature PCB Relay 8 - 10 - 12 - 16 A











Technical description:

Miniature PCB Relays, PCB/Plug-in – 3.5 mm pinning, 1 pole, NO, 12 A, AgNi, AC coil, 230 V, operating from 184 to 253 V, rated power 1.2 VA, resistance 28000 Ω, consumption 5 mA, holding voltage 184 V, must drop-out voltage 46 V, option: Pin length 5.3 mm (Plug-in relays), version: Flux proof (RT II), ambient temperature from -40 to +85 °C

This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

[BROWSE PRODUCT PAGE](#)

Technical Features:

Ambient temperature range:	-40...85 °C
Commercial description:	Miniature PCB relay, 1 CO 12 A. PCB mount (3.5 mm pin pitch) or plug-in with 95 Series sockets, DC coils (650 mW or 500 mW) and AC coils. Variant with Cadmium-free contacts. 8 mm, 6 kV (1.2/50 µs) insulation between coil and contacts. Complies with the glow wire test according to EN 60335-1..
Contact configuration:	1 pole, NO
Dimensions:	12.4x25x29 mm
Electrical life:	200000 cycles
Insulation coil/contacts:	6 kV
Nominal voltage ac:	230 V
Operating range ac:	184...253 V
Rated contact voltage:	250 V AC
Rated current (contacts):	12 A
Rated power ac:	1.2 VA
Supply:	AC coil
Certifications and quality approvals (according to type):	    RINA    

The information, technical details, data and features contained in this document are subject to change or modification at any time.
It is for information purposes only and does not form the basis of a contract.

Need more information?
[Contact our sales](#) [Find a dealer](#)